

## POLYIMIDE FILM INSULATED WIRE

Characteristics		
<b>Conductor material</b>	<ul style="list-style-type: none"> <li>• Copper soft or with controlled proof stress (CPR)</li> <li>• Aluminium soft</li> </ul>	
<b>Type of insulation</b>	Options: <ul style="list-style-type: none"> <li>• polyimide film, FEP coated and heatsealed with or without insulation of mixed polyester and glass yarn</li> </ul>	
<b>Insulation options</b>	<ul style="list-style-type: none"> <li>• overlapped up to max. 66%</li> <li>• 1 film</li> <li>• 2 layers cross lapped</li> </ul>	
<b>Standards</b>	Internal standard or Customer Specification	
<b>Standard range of dimensions</b>	Copper	Aluminium
<b>cross-section (mm<sup>2</sup>)</b>	2 to 120	5 to 120
<b>width (mm)</b>	2,00 to 20,00	4,00 to 20,00
<b>thickness (mm)</b>	1,00 to 6,00	2,00 to 6,00
<b>ratio w/t</b>	< 10	< 10
<b>Applications</b>	<ul style="list-style-type: none"> <li>• Motors for heavy-duty applications</li> <li>• Traction motors</li> <li>• Generators</li> </ul>	